




White



Cream



Burlap




Fog




Wheat



Smoke



Lotion



Sunshine



Camel




Pebble



Cinnamon



Aqua




Mist



Buckskin




Pecan



Pine



Cherry



Denim




Rain



Taupe



Walnut



Ivy



Port



Black

Construction	Values	Test Method
Surface Composition	PVC	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Finished Width	54" min.	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Stain Resistant Top Coat	Yes	
Cleaning Code	WS	

Performance	Values	Test Method
Grab Tensile	85 lbs./in. × 75 lbs./in. min.	ASTM D 751-06
Trap Tear	20 lbs./in. × 27 lbs./in. min.	ASTM D 751-06
Seam Strength	35 lbs./in. × 30 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	7.5% × 18%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03 (2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Cold Crack Resistance	-20°F - Pass	CFFA-6a
Crock Resistance	Dry - 4; Wet - 4	AATCC 8-2007
Wyzenbeek Abrasion	1,300,000 cycles, #10 cotton duck	ASTM D 4157
Colorfastness to Light	650 hours	ASTM D 4329

Flammability	Environmental	
California Technical Bulletin 117-2013, Sec. 1	Pass	1. No anti-microbial additives
FMVSS/CMVSS #302	Pass	2. Does not contain PFAS, PFOA
IMO A.652(16)8.2	Pass	3. Prop 65 compliant
NFPA 260	Pass	4. No chemical flame retardants, CA AB2998 compliant
U.F.A.C. Class I	Pass	5. RoHS compliant – Phthalate free

Suitable Applications Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.

