




Daisy



Pearl



Swan



Driftwood




Sand




Khaki




Cameo



Wheat



Sky



Cool Gray



Grove



Taupe



Saddle



Topaz



Dusk



Turquoise



Spring Green




Sumac



Anthracite




Maple



Slate




Aqua



Pine



Wine



Midnight



Terra Cotta



Cove



Peacock

Construction	Values	Test Method
Surface Composition	100% Polyurethane	
Backing Composition	50% Nylon / 50% Polyurethane	ASTM D 751-06
Finished Width	54" Width	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	

Performance	Minimum Values	Test Method
Grab Tensile	120 lbs./in. × 120 lbs./in. min.	ASTM D 751-06
Trap Tear	40 lbs./in. × 40 lbs./in. min.	ASTM D 751-06
Seam Strength	120 lbs./in. × 120 lbs./in. min.	ASTM D 751-06
Adhesion	5 lbs./in. × 5 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	4% × 12%	ASTM D 751-06
Puncture Resistance	110 lbf	ASTM D 751-06
Flex Resistance	25,000 cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	Wet-4; Dry-4	AATCC 8-2007
Hydrolysis Resistance	7 weeks	ASTM D 3690-02; ISO 5423: 1992 E
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-13
UV Stability	200 hours (4-5)	AATCC 16
Cold Crack (#5 roller)	-20°F	CFFA-6a

Flammability	Environmental	
California Technical Bulletin 117-2013, Sec. 1	Pass	1. No anti-microbial additives
IMO A.652(16) 8.2 & 8.3	Pass	2. Does not contain PFAS, PFOA
MVSS #302	Pass	3. Prop 65 compliant
NFPA 260	Pass	4. No chemical flame retardants, CA AB2998 compliant
U.F.A.C. Class I	Pass	5. REACH, RoHS, and LEED compliant

**Suitable Applications** Hospitality, Contract, Residential, RV

### Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.

